AXOLIFT: Offering smart and safe alternatives to ladders

Manulift 200

Up to 4 meters in total safety

MANULIFT 200: MANUAL MAST LIFT

- Without batteries.
- No power consumption or need to be recharged
- Without CO2 emission or gas leakage
- No hydraulic system therefore no risk of leakage
- Low cost maintenance
- Possible use 24h/24 7d/7

MANULIFT 200 platform is a full mechanical, versatile, robust and simple to use vertical mast platform, ideal for many applications - from construction to industries.

- Lightweight
- Completely manual
- Automatic stabilization
- Passes easily through standard doors
- Patented lifting mechanism* without power source



Automatic breaking system.


Foot brake on rear wheel.

Saloon-door style entry gates.

Attachment point.

Emergency lowering system.





MANULIFT 200 technical data

Dimension:

Max. Working Height: 4,00 m Max. Platform Height: 2,00 m Overall Width: 735 mm Overall Length: 1180 mm Stowed Height: 1670 mm 740 x645 mm Work Platform: **Ground Clearance:** 62 mm

Performance: 125kg / 1 pers. Platform Capacity SWL: Tool Tray Capacity: 20 kg Max. Force To Be Exerted On The Handle: -5 daN 0°- Internal Use Allowable Cant: 0km/h- Internal Use Max. Wind Speed: High resistance paint Orange RAL 2000 Marking and conformity CE- Compliance with the standard EN 280

Weight:

Gross Weight:



735 mm

1180 mm



275 kg

- Mer än bara ställning -